

■ SPECIFICATIONS

	Range	UT320A	UT320D
Temperature measurement (K)	-50°C~1300°C	±(0.5%+1)	±(0.5%+1)
Temperature measurement (J)	-50°C~1200°C	±(0.5%+1)	±(0.5%+1)
Features			
Display mode		Single	Dual
Auto power off		√	√
Low battery indication		√	√
Difference measurement (T1-T2)			√
Data hold		√	√
°C/°F selection		√	√
MAX/MIN/AVG		√	√
Mode selection (K/J)		√	√
Backlight		√	√
Drop test	1m	√	√
Operating temperature	0°C~40°C		
Operating humidity	≤80%RH		



● UT320D

■ GENERAL CHARACTERISTICS

Power	1.5V battery (R03) x 3
Display	37.4mm x 36.4mm
Product color	Red and grey
Product net weight	60g
Product size	120mm x 53mm x 28mm
Standard accessories	K-type temperature probe, batteries
Standard individual packing	Gift box, English manual
Standard quantity per carton	20pcs
Standard carton measurement	332mm x 225mm x 200mm
Standard carton gross weight	3.4kg

UT320A and UT320D are single and double channel contact type thermometers respectively. These highly accurate thermometers have a wide temperature range. UT320D can also calculate the temperature difference of its two channels. UT320 can be used with any K or J temperature probe.

